



Sensor Flushometer

EBV89A-CP

Product description

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Electrical Override, Battery, Infrared, Exposed Sensor Urinal/Water Closet Retrofit Flushometer.

Compliances & Certifications



(BREEAM Water Credit, Green Globes Water)

Code 0325105

Finish

 Polished Chrome (CP)

Downloads

- [Side Mount Operator Unit Installation Instructions.pdf](#)
- [Optima SMO Installation Instructions.pdf](#)
- [EBV-89A Side Mount Repair and Maintenance Guide.pdf](#)
- [Retrofits Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Polished Chrome (CP)
- Power Type: Battery
- Fixture Type: Urinal/Water Closet
- Fixture Connection: Top Spud
- Override: Electrical

Features

- Battery powered
- Estimated 3 year battery life

Electrical specifications

- Control Circuit:
 - Solid State
 - 6 VDC Input
 - 24 Hour Sentinel Flush
- Sensor Range: 22"-42" (559 - 1067mm)

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EBV89A product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

Side Mount Operator unit shown on an existing Sloan Regal Model 110/111 Closet Flushometer

