NA-413-1 Cut Sheet

AUTOMATIONDIRECT.com
www.automationdirect.com



Penn-Union neutral bar, tin-plated aluminum, 17 openings, 15 circuits, mounting hole position 1 and 17, copper or aluminum, AL9CU.

For complete product information, please see this item on our store at the following link:

https://www.automationdirect.com/pn/NA-413-1

Technical Specifications

Brand	Penn-Union
Item	Neutral bar
Material	Tin-plated aluminum
Number Of Openings	17
Number Of Circuits	15
Mounting Hole Position	1 and 17
Conductor Size	14–4 AWG stranded copper, 14–8 AWG solid copper, 8–4 AWG stranded aluminum and 12–8 AWG solid aluminum
Conductor Material	Copper or aluminum
Tightening Torque	14–8 AWG 20 in·lb copper or aluminum and 6–4 AWG 31 in·lb copper or aluminum
Dual Rating	AL9CU
Application	Neutral and grounding

Agency Approvals

UL Listed File #	E73393
UL Recognized File #	E12822
UL Hazardous File #	None
CSA File #	None
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement

Dimensional Drawings

2D Drawing PDF Link:
https://cdn.automationdirect.com/static/drawings/2d/NA-413-1.pdf
See store item page for other formats.