HOBART

Product Selection Guide

COMMERCIAL DISHWASHERS

Glasswashers

LXGeR advansys



30 (light)
24 (normal)

0.62

12"

LXGePR advansys



30 (light)
24 (normal)

1.14

12"

LXE ADA compliant models available.

ENERGY STAR

All Hobart Dishwashers noted in this product guide are ENERGY STAR® certified with the exception of the Centerline™ products.

Undercounters

Centerline™ CUH/CUL



24

0.84

14.46"

LXeH/LXeC



32 (high temp)
34 (low temp)

0.74

17"

LXeR advansys



30 (light)
24 (normal)
13 (heavy)

0.62

17"

Door Types

AM16SCB



72

0.67

17"

Centerline™ CDH/L



51

0.73 (CDH)
0.86 (CDL)

18"

AMTL



80

0.62 (both sections)

17" (Upper)
8.8" (Lower)

AM16(T)/AM16VL(T)-BAS



60 (AM16(T)-BAS)
45 (AM16VL-BAS)
40 (AM16VLT-BAS)

0.67

17" (base)
27" (tall)

AM16-ASR/AM16T-ASR



52

0.67

17" (base)
27" (tall)

AM16VL-ADV/AM16VLT-ADV advansys



40 (AM16VL-ADV)
36 (AM16VLT-ADV)

0.67

17" (base)
27" (tall)

Key

Racks per hour
Gallons per rack
Door opening (inches)
Tank count
Gallons per minute
Dishes per hour
High Temp
Low Temp
ASR
Ventless
DWER

Prepwashers

PW10/PW20



20 (2 min.)
12 (4 min.)
8 (6 min.)

1.2 (PW10eR)
2.8 (PW20eR)

33.79"

PW10eR/PW20eR advansys



13 (2 min.)
9 (4 min.)
7 (6 min.)

1.2 (PW10eR)
2.8 (PW20eR)

33.79"

PWV



20 (2 min.)
12 (4 min.)
8 (6 min.)

1.2

28"

PWVeR advansys



13 (2 min.)
9 (4 min.)
7 (6 min.)

1.2

28"

Rack Conveyors






CLeN advansys

- ASR (Automatic Soil Removal)
- DWeR (Drain Water Energy Recovery)
- "Intelligent Dwell" Pot and Pan Mode
- Customized Delime Notification
- Ergonomically designed handles

CLeN Energy Recovery







- DWeR (Drain Water Energy Recovery)
- "Intelligent Dwell" Pot and Pan Mode
- Customized Delime Notification
- Ergonomically designed handles

CLeN Ventless

- Ventless Operation
- "Intelligent Dwell" Pot and Pan Mode
- Customized Delime Notification
- Ergonomically designed handles

CLeN Base

- "Intelligent Dwell" Pot and Pan Mode
- Customized Delime Notification
- Ergonomically designed handles

44" CLeN*	54" CLeN	64" CLeN	66" CLeN*	76" CLeN	86" CLeN
					
202	245	342	202	245	342
0.62	0.56	0.39	0.62	0.56	0.39
Single	Single	Double (Power Scrapper & Wash)	Double (Power Scrapper & Wash)	Double (Wash & Rinse)	Triple (Power Scrapper, Wash & Rinse)

Advansys® rack conveyor models include an external ASR basket (not shown), which adds 10" to the machine footprint (ASR basket does not exceed vent hood dimensions).
*Ventless Model Available – uses the same tabling dimensions as base models, though come standard with 10" wide vent cowls.

CHOOSE THE BEST DISHMACHINE FOR YOUR APPLICATION

Use the product finder to identify the ideal washing system.

HOBART	VOLUME (MEALS PER HOUR)						DISHROOM AREA/SPACE AVAILABLE			
	Up to 50	50 to 250	250 to 400	400 to 750	750 to 1500	1500 plus	25" x 25"	44" x 30"	64" x 30"	9½' x 26'
Glasswasher							•			
Undercounter	•	•					•			
Door Type		•	•					•		
Prep Washer		•	•						•	•
Rack Conveyor			•	•	•			•	•	•
Flight Type					•	•				

Flight Type



FT1000e advansys

- 14,316
- 58
- 0.97
- Ventless
- Energy Recovery
- ASR (Automatic Soil Removal)
- Auto Delime
- Auto Clean
- Dual Rinse
- Blower dryer included
- Short model available

FT1000e Energy Recovery

- 14,316
- 58
- 0.97
- Energy Recovery
- ASR (Automatic Soil Removal)
- Auto Delime
- Auto Clean
- Dual Rinse
- Short model available

FT1000e Base

- 14,316
- 58
- 0.97
- ASR (Automatic Soil Removal)
- Auto Delime
- Dual Rinse
- Short model available

All CLeN and FT1000e models are ENERGY STAR® certified ENERGY STAR Award

ENERGY STAR AWARD 2021
PARTNER OF THE YEAR
Sustained Excellence

14 CONSECUTIVE
PARTNER OF THE YEAR AWARDS

F40598 (01/22) ©2022 Hobart
As continued product improvement is a policy of Hobart, specifications are subject to change without notice.