

Commercial hand blenders XM



XS - 10

XM-12



S - 20

XM-21



XM-22



B-20



MB-21

M - 30

XM-31



XM-32



XM-33



B-30



MB-31

L - 50

XM-51



XM-52



B-50



MB-51

XL - 70

XM-71



XM-72



Watch Video
on Youtube



Professional
performance



Enhanced UX

Maximum comfort
for the user



Built-to-last



Specifications

Professional performance



Versatility without add-on tools

As hand blender

Ideal for achieving the most subtle and delicate blending: airy consistencies, smooth purées, etc.

The blade, the blade protector and the range of speeds available make it ideal for achieving anything from the most demanding blending to more delicate and airy emulsions, all in a fast and comfortable way and without the need for add-on tools.

As whisk

The whisk is ideal for whipping cream, preparing meringues, chantilly, mayonnaise, Genovese sauce, omelettes, crêpes, soufflés, etc. all in a fast and comfortable way and without the need for add-on tools.



Professional performance

Hand blender

PROFESSIONAL
PERFORMANCE

ENHANCED
UX

BUILT
TO LAST

SPECIFICATIONS



Y-Blade

The **Y-Blade**, professional and with **three very sharp blades of tempered steel** with a long-duration cutting edge, has inclinations which have been studied in order to achieve a perfect result with each elaboration. Thanks to the three blades, **less time and less motor effort is required** to obtain the desired texture.



Vario speed

All of the hand mixer & blender combo machines, all of the whisks and the XS and S hand blenders have variable speed.



Models for all types of productions

As hand blender

The XM range is geared towards working with maximum comfort in containers ranging from 10.6 qt. to 264 qt. in capacity.

As whisk

The beaters from the XM range are designed to work in containers ranging from 32 qt. to 85 qt. in capacity. They are able to beat up to 80 egg whites.



Optional arm

All of the XM models can be used with more than one mixer arm in different sizes, making the machine more versatile. Also, the S, M and L ranges can also be used with a whisk.



Enhanced UX

Maximum comfort for
the user



Logical and manageable size

◀ All of the XM models are designed to be easy to handle for the user. They therefore have a logical size within their range.



Ergo-design & bi-mat-grip



The external casing, made in two materials, allows an ergonomic hold with an anti-slip grip and the handle features optimum inclination in order to minimise fatigue.



Click-on-arm



The arm is **detachable** with quick fastening due to the safety restraint system and the “click” which indicates the locked position.

Hand blender

Hood designed to avoid splashes

The careful
design of the hood
avoids splashes
during work.



Intuitive use



The XM range showcases extremely simple and intuitive handling with light indicators to show whether the machine is connected to the mains.

Built-to-last

Durability guarantee



Professional performance

Robustly constructed, all models from the XM range are manufactured with materials of the highest quality and offer maximum motor power in a compact size. They are capable of carrying out prolonged work without the casing overheating.



Life-plus



The XM models are equipped with a motor which has passed all of the most demanding usage tests.

Studied geometry

The exterior shape of the casing is **designed to avoid it rolling and falling** from the work surface.

Easy to clean

Thanks to the ease of assembly and disassembly of the arm, cleaning it is extremely easy and can be done under the tap.

Moreover, the arm of XM-12 can be washed in the dishwasher.



Approved by NSF



All the models are standard 8 NSF certified, which is a hygiene and safety guarantee.

Specifications

PROFESSIONAL PERFORMANCE | ENHANCED UX | BUILT TO LAST | SPECIFICATIONS



Range	XS - 10	S - 20			
Model	XM-12	XM-21	XM-22	MB-21	B-20
Total loading	0.33 Hp	0.41 Hp	0.41 Hp	0.41 Hp	0.41 Hp
Speed, min-max	1500 rpm - 15000 rpm	1500 rpm - 15000 rpm	1500 rpm - 15000 rpm	1500 rpm - 15000 rpm	200 rpm - 1800 rpm
Electrical supply	120 V / 50-60 Hz / 1 ~ (1.5A)				
Hand blender function					
Maximum recipient capacity	10.6 qt.	13 qt.	16 qt.	13 qt.	--
Blade guard diameter	2.56"	3.23"	3.23"	3.23"	--
Liquidising arm length	8.8"	9.84"	11.8"	9.84"	--
Total length	17.6"	20.24"	2.52"	20.24"	--
Whisk function					
Capacity (egg whites)	--	--	--	2 - 30	2 - 30
Revolving arm length	--	--	--	12.05"	12.05"
Total length (with revolving arm)	--	--	--	22.44"	22.44"
Net weight					
Net weight	3.1lbs.	5.1lbs.	5.3lbs.	5.8lbs.	5.78lbs



Web



Spec sheet



Web



Spec sheet



Web



Spec sheet



Web



Spec sheet



Web



Spec sheet



Specifications

PROFESSIONAL PERFORMANCE | ENHANCED UX | BUILT TO LAST | SPECIFICATIONS



Range	M - 30					L - 50				XL - 70	
Model	XM-31	XM-32	XM-33	MB-31	B-30	XM-51	XM-52	MB-51	B-50	XM-71	XM-72
Total loading	0.54 Hp	0.54 Hp	0.54 Hp	0.54 Hp	0.54 Hp	1.1 Hp	1.1 Hp	1.1 Hp	1.1 Hp	1.2 Hp	1.2 Hp
Speed, min-max	12000 rpm	12000 rpm	12000 rpm	1500 rpm - 12000 rpm	200 rpm - 1500 rpm	12000 rpm	12000 rpm	1500 rpm - 12000 rpm	200 rpm - 1500 rpm	12000 rpm	12000 rpm
Electrical supply	120 V / 50-60 Hz / 1 ~ (1.5A)										
Hand blender function											
Maximum recipient capacity	32 qt.	48 qt.	63 qt.	32 qt.	--	85qt .	127 qt.	85 qt.	--	211 qt.	264 qt.
Blade guard diameter	3.44"	3.44"	3.44"	3.44"	--	3.87"	3.87"	3.87"	--	4.85"	4.85"
Liquidising arm length	12.05"	14.41"	16.54"	12.05"	--	16.50"	20.43"	16.50"	--	21.22"	24.80"
Total length	24.17"	26.54"	28.66"	24.21"	--	29.92"	33.86"	29.92"	--	34.64"	38.19"
Whisk function											
Capacity (egg whites)	--	--	--	2 - 50	2 - 50	--	--	2 - 80	2 - 80	--	--
Revolving arm length	--	--	--	15.59"	15.59"	--	--	15.94"	15.95"	--	--
Total length (with revolving arm)	--	--	--	27.8"	27.8"	--	--	29.37"	29.37"	--	--
Net weight											
Net weight	7.36lbs.	7.63lbs.	8lbs.	7.6lbs.	7.58lbs.	10.25lbs.	10.69lbs.	10.3lbs.	9.72lbs.	11lbs.	11.42lbs

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet


Web
 Spec sheet

Web
 Spec sheet

Web
 Spec sheet







UNE-EN ISO 9001

SAMMIC, S.L. · Basarte, 1 · 20720 AZKOITIA (Gipuzkoa) · SPAIN

