



Bottom mounted reach-In Glass door refrigerator

AN Series

CHARACTERISTICS



Structure

AISI 430 stainless steel.
Galvanized metal back cover plate.
4 inch casters diameter. Front casters with brake.
Lift-up control panel for easy access to condenser unit.
Lock system.
Wide rounded corners to aid cleaning.
Drain inside the cabinet.



Certifications

Infirco is audited and certified by the international organization **INTERTEK** in accordance with **UL 471** and **NSF 7**.

Tray sliders
are compatible
with 18"x 26"
and 12"x 20"
sheet pans

IRR-AN23CR

IRR-AN49CR

Reinforced wire shelves

Sealed interior floors and
rounded cabinet corners

MOD.



Overall Dimensions

Doors

Shelves

(°F)

(ft³)

(HP)

115V

(Lbs)

(\$)

IRR-AN23CR	27	31-3/8	83-1/2	1	4	33°F/38°F	23.0	1/3	3.8	430	\$8.316
IRR-AN49CR	54-1/2	31-3/8	83-1/2	2	8	33°F/38°F	49.0	1/3	4.9	600	\$12.104
IRR-AN67CR	82	31-3/8	83-1/2	3	12	33°F/38°F	67.0	1/2	6.2	723	\$14.936

Height already includes 5-1/8" for casters

Bottom mounted reach-In Glass door refrigerator

AN Series

TECHNICAL CHARACTERISTICS



Refrigeration

Air cooled condensation system.

Forced air evaporation system.

Energy-saving non-electric **condensate pan**.

Evaporators treated with anti-corrosion polyester Epoxy.



Lighting

Highly efficient LED lighting incorporated.



RGB LED lighting
(option)

IRR-AN67CR



STANDARD FEATURES

REFRIGERATION	Forced air refrigeration and Capillary system	
ELECTRICAL	Cord and NEMA 5-15P plug, electrical connection is 115V / 1ph / 60Hz	
DOE	Hydrocarbon R-290	
DOORS	Built-in double Thermopane glass door	
OPTIONS Section 10 [Accessories & parts]	Stainless Steel wire shelves	Additional slide kits
	Stainless Steel tray divider	Set of 6" legs, height adjustable from 5" to 8"