



 **MAXX COLD**

 **MAXX COLD**  
*X-series*

 **MAXX COLD**  
*SELECT SERIES*

## REFRIGERATORS & FREEZERS

Maxx Cold offers a robust line of refrigeration options to meet any budget or application. Choose from an array of refrigerators and freezers including 1, 2 and 3 door upright units featuring stainless steel, glass doors in either top or bottom mount designs. Undercounter models, as well as solid and glass-top Chest Freezers are also available.

# BOTTOM-MOUNT REACH-IN REFRIGERATORS & FREEZERS



**MCR-23FDHC**  
**MCF-23FDHC**  
26.75"W x 31"D x 82.75"H



**MCR-49FDHC**  
**MCF-49FDHC**  
54"W x 31"D x 82.75"H



**MCR-72FDHC**  
**MCF-72FDHC**  
81"W x 31"D x 82.75"H

## Refrigerators:

**MCR-23FDHC** - Upright reach-in refrigerator; stainless steel exterior

**MCR-49FDHC** - Upright reach-in refrigerator; stainless steel exterior

**MCR-72FDHC** - Upright reach-in refrigerator; stainless steel exterior

## Freezers:

**MCF-23FDHC** - Upright reach-in freezer; stainless steel exterior

**MCF-49FDHC** - Upright reach-in freezer; stainless steel exterior

**MCF-72FDHC** - Upright reach-in freezer; stainless steel exterior

## All Models Feature:

- Self-closing door(s) with easy to grip recessed handle(s)
- Automatic interior lighting
- Lock and key set for security
- Equipped with four (4) or six (6) 5" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for five minutes
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Polyurethane foam insulation provides outstanding thermal regulation and energy efficiency



| MODEL      | EXTERNAL DIMENSIONS                            | INTERNAL DIMENSIONS                             | NET CAPACITY           | HOLDING TEMPERATURE RANGE         | AMP DRAW | HP  | UNIT WEIGHT         | REFRIGERANT AND CHARGE SIZE | DOORS / SHELVES | ELECTRICAL        |
|------------|------------------------------------------------|-------------------------------------------------|------------------------|-----------------------------------|----------|-----|---------------------|-----------------------------|-----------------|-------------------|
| MCR-23FDHC | 26.75" x 31" x 82.75"<br>(680 x 787 x 2102 mm) | 22.8" x 24.1" x 53.7"<br>(578 x 613 x 1364 mm)  | 18.9 Cu Ft<br>(535 L)  | 33°F to 41°F<br>(1°C to 5°C)      | 2.0A     | 1/4 | 271 lbs<br>(123 kg) | R-290a<br>2.53 oz (72 g)    | 1 / 3           | 115V / 60Hz / 1Ph |
| MCR-49FDHC | 54" x 31" x 82.75"<br>(1372 x 787 x 2102 mm)   | 49.8" x 24.1" x 53.7"<br>(1264 x 613 x 1364 mm) | 42.8 Cu Ft<br>(1212 L) | 33°F to 41°F<br>(1°C to 5°C)      | 2.4A     | 1/4 | 397 lbs<br>(180 kg) | R-290a<br>3.46 oz (98 g)    | 2 / 6           | 115V / 60Hz / 1Ph |
| MCR-72FDHC | 81" x 31" x 82.75"<br>(2057 x 787 x 2102 mm)   | 77.3" x 24.1" x 53.7"<br>(1963 x 613 x 1364 mm) | 66.7 Cu Ft<br>(1889 L) | 33°F to 41°F<br>(1°C to 5°C)      | 5.5A     | 1/2 | 634 lbs<br>(287 kg) | R-290a<br>5.22 oz (148 g)   | 3 / 9           | 115V / 60Hz / 1Ph |
| MCF-23FDHC | 26.75" x 31" x 82.75"<br>(680 x 787 x 2102 mm) | 22.8" x 24.1" x 53.7"<br>(578 x 613 x 1364 mm)  | 18.9 Cu Ft<br>(535 L)  | -10°F to 10°F<br>(-23°C to -12°C) | 5.6A     | 1/2 | 284 lbs<br>(129 kg) | R-290a<br>2.33 oz (66 g)    | 1 / 3           | 115V / 60Hz / 1Ph |
| MCF-49FDHC | 54" x 31" x 82.75"<br>(1372 x 787 x 2102 mm)   | 49.8" x 24.1" x 53.7"<br>(1264 x 613 x 1364 mm) | 42.8 Cu Ft<br>(1212 L) | -10°F to 10°F<br>(-23°C to -12°C) | 4.6A     | 1/2 | 403 lbs<br>(183 kg) | R-290a<br>4.44 oz (126 g)   | 2 / 6           | 115V / 60Hz / 1Ph |
| MCF-72FDHC | 81" x 31" x 82.75"<br>(2057 x 787 x 2102 mm)   | 77.3" x 24.1" x 53.7"<br>(1963 x 613 x 1364 mm) | 66.7 Cu Ft<br>(1889 L) | -10°F to 10°F<br>(-23°C to -12°C) | 9.9A     | 1   | 650 lbs<br>(295 kg) | R-290a<br>5.08 oz (144 g)   | 3 / 9           | 220V / 60Hz / 1Ph |