



 **MAXX COLD**

 **MAXX COLD**
X-series

 **MAXX COLD**
SELECT SERIES

REFRIGERATORS & FREEZERS

Maxx Cold offers a robust line of refrigeration options to meet any budget or application. Choose from an array of refrigerators and freezers including 1, 2 and 3 door upright units featuring stainless steel, glass doors in either top or bottom mount designs. Undercounter models, as well as solid and glass-top Chest Freezers are also available.

TOP-MOUNT REACH-IN REFRIGERATORS & FREEZERS



MXCR-19FDHC
MXCF-19FDHC

26.75"W x 31.5"D x 77.6"H



MXCR-23FDHC
MXCF-23FDHC

26.75"W x 32.7"D x 82.25"H



MXCR-49FDHC
MXCF-49FDHC

54"W x 32.7"D x 82.25"H



MXCR-72FDHC
MXCF-72FDHC

81"W x 32.7"D x 82.25"H

Refrigerators:

MXCR-19FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-23FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-49FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-72FDHC - Upright reach-in refrigerator; stainless steel exterior

Freezers:

MXCF-19FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-23FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-49FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-72FDHC - Upright reach-in freezer; stainless steel exterior

All Models Feature:

- Self-closing door(s) with wasy to grip recessed handle(s)
- Field reversible door (single door models only)
- Automatic interior lighting
- Lock and key set for security
- Equipped with four (4) or six (6) 5" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for three minutes
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXCR-19FDHC	25.2" x 31.5" x 77.6" (640 x 800 x 1970 mm)	20.25" x 28.7" x 61.8" (514 x 730 x 1570 mm)	19 Cu Ft (538 L)	34°F to 41°F (1°C to 5°C)	3A	291 lbs (132 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXCR-23FDHC	26.8" x 32.7" x 82.25" (681 x 831 x 2090 mm)	21.9" x 26.5" x 52.1" (556 x 673 x 1324 mm)	23 Cu Ft (651 L)	34°F to 41°F (1°C to 5°C)	3A	311 lbs (143 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXCR-49FDHC	53.9" x 32.7" x 82.25" (1369 x 831 x 2090 mm)	49.1" x 26.5" x 52.1" (1246 x 673 x 1324 mm)	49 Cu Ft (1387 L)	34°F to 41°F (1°C to 5°C)	4.5A	536 lbs (244 kg)	R-290A 3.7 oz (105 g)	2 / 6	115V / 60Hz / 1Ph
MXCR-72FDHC	81" x 32.7" x 82.25" (2057 x 831 x 2090 mm)	76.1" x 26.5" x 52.1" (1933 x 673 x 1324 mm)	72 Cu Ft (2039 L)	34°F to 41°F (1°C to 5°C)	7A	639 lbs (291 kg)	R-290A 5.29 oz (150 g)	3 / 9	220V / 60Hz / 1Ph
MXCF-19FDHC	25.2" x 31.5" x 77.6" (640 x 800 x 1970 mm)	20.25" x 28.7" x 61.8" (514 x 730 x 1570 mm)	19 Cu Ft (538 L)	-10°F to 10°F (-23°C to -12°C)	8A	296 lbs (134 kg)	R-290A 3.88 oz (110 g)	1 / 3	115V / 60Hz / 1Ph
MXCF-23FDHC	26.8" x 32.7" x 82.25" (681 x 831 x 2090 mm)	21.9" x 26.5" x 52.1" (556 x 673 x 1324 mm)	23 Cu Ft (651 L)	-10°F to 10°F (-23°C to -12°C)	8A	336 lbs (140 kg)	R-290A 3.88 oz (110 g)	1 / 3	115V / 60Hz / 1Ph
MXCF-49FDHC	53.9" x 32.7" x 82.25" (1369 x 831 x 2090 mm)	49.1" x 26.5" x 52.1" (1246 x 673 x 1324 mm)	49 Cu Ft (1387 L)	-10°F to 10°F (-23°C to -12°C)	9A	502 lbs (160 kg)	R-290A 5.29oz (150 g)	2 / 6	115V / 60Hz / 1Ph
MXCF-72FDHC	81" x 32.7" x 82.25" (2057 x 831 x 2090 mm)	76.1" x 26.5" x 52.1" (1933 x 673 x 1324 mm)	72 Cu Ft (2039 L)	-10°F to 10°F (-23°C to -12°C)	9A	601 lbs (195 kg)	R-290A 5.29oz (150 g)	3 / 9	230V / 60Hz / 1Ph