



 **MAXX COLD**
X-series

 **MAXX COLD**
SELECT SERIES

UNDERCOUNTER REFRIGERATORS AND FREEZERS

Our undercounter refrigeration options pair reliable cold storage and sturdy construction with valuable countertop space. A variety of sizes are available in both refrigerators and freezers to meet your needs.



MXCR27U-FBHC
27.5"W x 30"D x 31.5"H

MXCR27UHC
MXCF27UHC
27.5"W x 30"D x 35.5"H

MXCR48UHC
MXCF48UHC
48.3125"W x 30"D x 35.5"H

MXCR60UHC
MXCF60UHC
60.375"W x 30"D x 35.5"H

MXCR72UHC
72.375"W x 30"D x 35.5"H

Refrigerators:

- MXCR27UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR27U-FBHC** - Undercounter refrigerator; stainless steel exterior
- MXCR48UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR60UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR72UHC** - Undercounter refrigerator; stainless steel exterior

Freezers:

- MXCF27UHC** - Undercounter freezer; stainless steel exterior
- MXCF48UHC** - Undercounter freezer; stainless steel exterior
- MXCF60UHC** - Undercounter freezer; stainless steel exterior

All Models Feature:

- Durable, easy to clean stainless steel exterior
- Painted aluminum interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Equipped with four (4) 3" swivel casters (2 with brakes)
- Solid state digital control system
- LED temperature display
- Accommodates full-size sheet pans
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane insulated walls and doors
- MXCR27U-FBHC: Compact front-breathing design accommodates tight spaces



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXCR27UHC	27.5" x 30" x 35.5" (699 x 762 x 911 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	6.5 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	1.5A	220 lbs (100 kg)	R-600a 2.47 oz (68 g)	1 / 1	115V / 60Hz / 1Ph
MXCR27U-FBHC	27.5" x 30" x 31.5" (700 x 760 x 800 mm)	23.4" x 16.6" x 20.7" (594 x 423 x 525 mm)	6.5 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	1.5A	243 lbs (110 kg)	R-600a 2.47 oz (68 g)	1 / 1	115V / 60Hz / 1Ph
MXCR48UHC	48.3125" x 30" x 35.5" (1227 x 762 x 911 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (140 kg)	R-600a 2.65 oz (75 g)	2 / 2	115V / 60Hz / 1Ph
MXCR60UHC	60.375" x 30" x 35.5" (1533 x 762 x 911 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	3.0A	352 lbs (160 kg)	R-600a 2.82 oz (80 g)	2 / 2	115V / 60Hz / 1Ph
MXCR72UHC	72.375" x 30" x 35.5" (1839 x 762 x 911 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	3.5A	430 lbs (195 kg)	R-290a 4.59 oz (130 g)	3 / 3	115V / 60Hz / 1Ph
MXCF27UHC	27.5" x 30" x 35.5" (699 x 762 x 911 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	6.5 Cu Ft (184 L)	-4°F to 10°F (-20°C to -12°C)	1.9A	224 lbs (102 kg)	R-290a 3.35 oz (95 g)	1 / 1	115V / 60Hz / 1Ph
MXCF48UHC	48.3125" x 30" x 35.5" (1227 x 762 x 911 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	-4°F to 10°F (-20°C to -12°C)	4.0A	310 lbs (141 kg)	R-290a 3.53 oz (100 g)	2 / 2	115V / 60Hz / 1Ph
MXCF60UHC	60.375" x 30" x 35.5" (1533 x 762 x 911 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	-4°F to 10°F (-20°C to -12°C)	5.0A	362 lbs (166 kg)	R-290a 3.53 oz (100 g)	2 / 2	115V / 60Hz / 1Ph