



 **MAXX COLD**
X-series

MERCHANDISERS

Showcase your cold beverages, food products and grab and go items with Maxx Cold Merchandisers. Our glass door Merchandisers provide excellent product visibility to help boost impulse sales, keep product at the right temperature and are energy efficient.

UPRIGHT MERCHANDISER REFRIGERATORS



MXM1-12RHC
25"W x 26"D x 62"H



MXM1-12RBHC
25"W x 26"D x 62"H



MXM1-16RHC
25"W x 26"D x 74.5"H



MXM1-16RBHC
25"W x 26"D x 74.5"H



MXM1-23RHC
27"W x 32"D x 79.5"H



MXM1-23RBHC
27"W x 32"D x 79.5"H

Models:

MXM1-12RHC - Reach-in refrigerator; white coated steel exterior

MXM1-12RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16RHC - Reach-in refrigerator; white coated steel exterior

MXM1-16RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23RHC - Reach-in refrigerator; white coated steel exterior

MXM1-23RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12RHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12RBHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RBHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23RHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23RBHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph