

# portable countertop induction range

models : **GS1681**



## FEATURES

- Durable glass top, stainless steel housing and molded plastic bottom
- Touch pad controls, 4 digit LED display, and digital timer
- 6 power levels
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 150° to 450°F
- Overheat protection
- Error code alert display
- Attached 5 1/2-foot power cord and plug, NEMA 5-15P
- Non-slip feet
- 10" diameter pan maximum

Take the high energy efficiency of induction cooking virtually anywhere—even on the road in mobile applications—with this ingenious, portable countertop unit. Combines versatile digital controls, pan detection with automatic empty-pan shutoff, and overheat protection to make this advanced method of cooking as easy as possible. The glass cooktop inside a stainless-steel housing maximizes durability. Features six power levels, with temperatures up to 450°F for all kinds of pans.



# portable countertop induction range

models : **GS1681**

## SPECIFICATIONS

Equipment (WxDxH) .....	12 <sup>1</sup> / <sub>16</sub> " x 14" x 2 <sup>3</sup> / <sub>4</sub> "
Equipment Weight .....	8 lbs
Shipping Weight .....	9 lbs
<b>Voltage</b> .....	<b>120</b>
<b>Wattage</b> .....	<b>1800</b>
<b>Amps</b> .....	<b>15</b>
<b>Plug Configuration</b> .....	<b>5-15P</b>



12<sup>1</sup>/<sub>16</sub>"

