CSC Water Filtration Systems

It All Starts with Great Water



CSC5AC00

CURTIS Water Filtration Systems

Curtis Water Filtration Systems are specifically designed for coffee brewing equipment. Advanced HydroBlend™ technology delivers effective scale and corrosion control, and enhanced filtration components provide superior chlorine taste and odor removal for a better tasting gourmet beverage. Plus, Curtis Filters feature an extra large filtration medium which provides proper water flow well past the recommended replacement cycle – eliminating clogged filters and unnecessary service calls.

Specifications

MODEL #	DESCRIPTION	RATED LIFE*	FLOW	SHIP WEIGHT**	SHIP CUBE**
CSC5AC00 with Head, 5" Filter	Chlorine & Sediment Removal, Scale Prevention	4,000 Gal.	0.8 GPM	11.0 lbs.	1.36 cu. ft.
CSC5CC00 5" Replacement Cartridge Only	Chlorine & Sediment Removal, Scale Prevention	4,000 Gal.	0.8 GPM	9.0 lbs.	1.36 cu. ft.
CSC10AC00 with Head, 10" Filter	Chlorine & Sediment Removal, Scale Prevention	10,000 Gal.	1.7 GPM	17.0 lbs.	1.23 cu. ft.
CSC10CC00 with 10" Replacement Cartridge Only	Chlorine & Sediment Removal, Scale Prevention	10,000 Gal.	1.7 GPM	15.0 lbs.	1.23 cu. ft.
CSC10AV00 with Head, 10" Vend Filter	Chlorine & Sediment Removal, Scale Prevention/OCS/VEND	10,000 Gal.	1.7 GPM	17.0 lbs.	1.23 cu. ft.
CSC10CV00 with 10" Vend Replacement Cartridge Only	Chlorine & Sediment Removal, Scale Prevention/OCS/VEND	10,000 Gal.	1.7 GPM	15.0 lbs.	1.23 cu. ft.
CSC10CF00 with 10" Fibredyne Cartridge Only	Chlorine Removal, Scale Prevention, Extra Sediment Loading	5,000 Gal.	1.0 GPM	15.0 lbs.	1.23 cu. ft.
CSC15AC00 with Head, 15" Filter	Chlorine & Sediment Removal, Scale Prevention	15,000 Gal.	2.0 GPM	23.0 lbs.	1.69 cu. ft.
CSC15CC00 with 15" Replacement Cartridge Only	Chlorine & Sediment Removal, Scale Prevention	15,000 Gal.	2.0 GPM	21.0 lbs.	1.69 cu. ft.

* Rated Life is for chlorine removal. To ensure proper control of scale, filters should be replaced every 6 months.
** Shipping Weight and Cube are per cases of 6.

Water Supply Requirements

WATER CONNECTOR	WATER PRESSURE	TEMP RANGE
3/8" FNPT	35-125 psi	35-100 °F

Features at a Glance

- Simple, small profile filter head installation
- Selection of cartridges to handle any equipment type
- Quick disconnect style cartridge for easy replacement
- Proven HydroBlend™ scale and corrosion control plus chlorine taste and odor removal – Provides better tasting, high quality beverages and reduced equipment maintenance costs



CSC15AC00



CSC10AC00