

# Horizontal Bottle Coolers (50" 65") Glass Door Back Bar Coolers (49" 61" 73")



**VPB50**



**VPB65**



**VP48G**



**VP60G**



**VP72G**

### Features

- Digital thermostat with LED display
- LED interior lighting
- Eco-friendly hydrocarbon R600A & R290 refrigerants
- 4 casters standard for easy maneuverability
- Fast forced air cooling
- Black corrosion resistant steel exterior, Stainless steel interior
- UL Energy verified, tested to NSF Standard 7

### Bottle Coolers

- Bottle cap opener with cap catcher
- Stainless steel countertop with integrated glass stops
- Stainless steel easy glide lids with locks for each lid
- Adjustable dividers included

### Back Bar Coolers

- Stainless steel top
- Self closing doors
- Vacuum-insulated double pane low E-glass doors
- Magnetic door gaskets requires no tools for cleaning or replacement
- Door locks
- Epoxy coated shelves supported by pilasters for easy adjustability



### Dimensional Data

Valpro Warranty\* 2 Year Parts & Labor, 5 Year Compressor\*

Model	Exterior Dimensions (Inches)	Interior Dimensions (Inches)	Net Storage Capacity	Net Weight	Crated Weight	Shipping Dimensions (Inches)
VPB50	49.4"Wx27"Dx35"H	45.3"Wx23"Dx17.1"H	14 cu. ft.	216 lbs.	247 lbs.	51.2"Wx29.1"Dx41.3"H
VPB65	64.3"Wx27"Dx35"H	60.2"Wx23"Dx17.1"H	19 cu. ft.	240 lbs.	286 lbs.	66.9"Wx29.1"D.1x41.3"H
VP48G	49.1"Wx24.4"Dx42.3"H	37.2"Wx21.6"Dx33.5"H	10.5 cu. ft.	252 lbs.	307 lbs.	50.6"Wx26"Dx44.1"H
VP60G	61.1"Wx24.4"Dx42.3"H	49.2"Wx21.6"Dx33.5"H	14 cu. ft.	286 lbs.	357 lbs.	62.6"Wx26"Dx44.1"H
VP72G	73.1"Wx24.4"Dx42.3"H	60.6"Wx21.6"Dx33.5"H	17 cu. ft.	331 lbs.	417 lbs.	74.7"Wx26"D.1x44.1"H

### Technical Data

\*Due to periodic changes in design and regulations the specifications in these sheets are subject to change without notice. Please visit our website or contact your sales representative for more detailed specification information.

Model	Doors	Shelves Dividers*	Temp. Range	Refrigerant	H/P	Voltage	Amps	(kWh/day) Energy consumption	Plug Type NEMA
VPB50	2 LID	2*	33°F-41°F	R600A	1/2	115V/60Hz/1	3	1.088	5-15P
VPB65	2 LID	3*	33°F-41°F	R600A	1/2	115V/60Hz/1	3	1.733	5-15P
VP48G	2	4	33°F-41°F	R290	2/5	115V/60Hz/1	3	1.685	5-15P
VP60G	2	4	33°F-41°F	R290	2/5	115V/60Hz/1	3	1.875	5-15P
VP72G	3	6	33°F-41°F	R290	1/2	115V/60Hz/1	3	1.986	5-15P